

PE 100

RUGGED TECHNOLOGY – COMPACT FOOTPRINT

Ruggedness, reliability, a wide range of applications and compact portability are all features of the PE 100.

Its range of applications is virtually unlimited. Available in three drive types with petrol engine, three-phase or single-phase AC motor, it is ideal for many uses, such as a breathing air compressor for diving groups or fire fighters or for rapid filling of cartridges for sports shooting or paintball cylinders.

The PE 100-TW sports shooting version has a non-bleed filling valve including adapter for filling cartridges and was designed specifically for sports shooting applications.

In the version with petrol engine, the PE 100 can be operated without an external power source in even the most remote locations. In the single-phase AC motor version, it can be powered from a household power supply.

- › 100 l/min
- › 225 or 330 bar
- › 2.2 kW (4.2 kW petrol version)
- › Available with three-phase motor, single-phase AC motor or petrol engine

FEATURES

- › Compact, low-weight system, easily transportable
- › The P 11 purification system designed especially for the PE 100 supplies pure breathing air in compliance with DIN EN 12021:2014¹
- › Many possible applications



PE 100, 300 bar model

**FOR ANYONE THAT WANTS TO RELY ON PURE, SAFE BREATHING AIR
IN MOBILE APPLICATIONS.**

OPTIONAL FEATURES

- › Motor protection switch for PE 100-TE
- › Intake telescope (standard with PE 100-TB) or intake manifold for attaching a suction hose

TECHNICAL DATA

Type	Charging rate ¹		Operating Pressure max.		Purification System	Number of Stages	Speed approx.	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig				rpm	Motor		
PE 100-TB	100	3.5	330	4780	P 11	3	2,300	Petrol engine 4-stroke	4.2	42	78 x 34 x 42
PE 100-TE	100	3.5	330	4780	P 11	3	2,300	Three-phase 400 V, 50 Hz	2.2	44	66 x 35 x 42
PE 100-TW	100	3.5	330	4780	P 11	3	2,300	Single-phase 230 V, 50 Hz ^{3,4}	2.2	44	66 x 35 x 42
PE 100-TW ² Sports Shooting Version	100	3.5	330	4780	P 11	3	2,300	Single-phase 230 V, 50 Hz ²	2.2	44	66 x 35 x 42

1 Measured by tank filling (10 l) from 0 - 200 bar / 2900 psig, ± 5%.

2 Filling valve without automatic vent including adapter for connecting adapters cartridges.

3 Plug dimension: Schuko plug. Plug only for units with 230 V / 50 Hz.

4 With integrated motor protection switch (only for 220/230/240 V).

