

Water  
Treatment  
SYSTEMS



## Chiller + Carbonator AquaMIX I: Top / Under

**T**ecnicomar Aquamix I (Top & Under versions) is a compact, high performing and automatic household system that supplies instant fresh water: chilled, sparkling and at room temperature.

Aquamix I Top is the only device that has got a front compartment for housing the front purification filter (optional) and CO<sub>2</sub> cylinder, with easy access that allows a simple maintenance by user. It has got quick and simplified connectors for easy oversink installation.

The Aquamix I Under model, with the same characteristics, is designed to be installed under the sink.

### TECHNICAL DATA AquaMIX I Top

Power supply (voltage / frequency)	230 V AC - 50 Hz
Power consumption (Watt / hour)	240 W / 0.75* - 0.65**
Type of refrigerant gas	HFC 134A
Dimensions (w x d x h - cm) - Weight (Kg)	38 x 24 x 52* / 47** - 23* / 24** Kg

### COOLING CAPACITY AquaMIX I Top

Liters of cold water per hour at 18 °C	19
Glasses of cold water of 200 cc per hour	95

\*: cooler + room temperature / \*\*: cooler + room temperature + carbonator



AquaMIX I Top



AquaMIX I  
Under  
-undersink-

- HIGH EFFICIENCY: SUPPLIES FROM 16 TO 19 LITRES/HOUR OF COLD AND SPARKLING WATER
- DIGITAL CONTROL WITH MULTI-FUNCTION DISPLAY FOR REGULATING THE WATER TEMPERATURE, CO<sub>2</sub> DIAGNOSIS AND FILTER CONDITION
- AUTO FILLING FOR SINGLE GLASS AND PITCHER EASILY PROGRAMMABLE
- FRONT PANEL IN STAINLESS STEEL AISI 304
- MAXIMUM NOISE OF COOLING SYSTEM DURING OPERATION: ONLY 32 dB
- STANDARD INSTALLATION KIT

### ACCESSORIES:

- FILTRATION AND CHLORINATION SYSTEM WITH UV STERILIZER
- REVERSE OSMOSIS WATER TREATMENT SYSTEM
- ADDITIONAL TAP FOR WATER AT ROOM TEMPERATURE, 3 OR 5 WAYS
- PREFILTER CARTRIDGE -20 x 14 cm-
- DISPOSABLE CO<sub>2</sub> CYLINDER -26 x 7 cm-
- RECHARGEABLE CO<sub>2</sub> CYLINDER (for AquaMIX I Under) -58 x 14 cm-

### TECHNICAL DATA AquaMIX I Under

Power supply (voltage / frequency)	230 V CA - 50 Hz
Power consumption (Watt / hour)	110 W
Type of refrigerant gas	HFC 134A
Dimensions (w x d x h - cm) - Weight (Kg)	38.5 x 24 x 32.5 - 12 Kg

### COOLING CAPACITY AquaMIX I Under

Liters of cold water per hour at 10 °C	34	25	19
Glasses of cold water of 200 cc per hour	170	125	95

\*: cooler + room temperature / \*\*: cooler + room temperature + carbonator



Tecnicomar S.p.A.

Head Office and Plant: 91025 MARSALA (TP), ITALY  
C.da Barbaro, 145/D - S.S. 115 Km. 36,4 - Phone (+39) 0923 969409 -  
Fax (+39) 0923 960235 - Subsidiary: 55049 VIAREGGIO (LU) - Via M. Coppino, 67  
Phone / Fax (+39) 0584 395408  
[www.tecnicomar.it](http://www.tecnicomar.it) - E-mail: [info@tecnicomar.it](mailto:info@tecnicomar.it)



The Tecnicomar chillers and carbonators are according to the Decree of the Italian Ministry of Health No. 443 of December 21, 1990 for domestic use water treatment

AquaMIX is equipped with filtering cartridges and membranes MADE IN U.S.A.



Data subject to changes without previous notice due to technological updates and commercial policies - © Tecnicomar S.p.A. 2015



GENERAL  
Marine  
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand  
Sales Ph +64 9 309 0048 · [sales@generalmarine.co.nz](mailto:sales@generalmarine.co.nz)  
Service Ph +64 9 368 0938 · [service@generalmarine.co.nz](mailto:service@generalmarine.co.nz)

[www.generalmarine.co.nz](http://www.generalmarine.co.nz)