



TRIDENT MARINE®

WHITE CORRUGATED VAC-HD WATER FILL (FDA)



146 Series

Trident Corrugated heavy wall vinyl hose with smooth tube. Low permeation & FDA (white only) compounds for potable water fill, holding tank pump out, bilge, drain, scupper lines and live well use. Hard PVC helix gives exceptional flexibility & bend radius. NOT RECOMMENDED FOR BELOW WATERLINE THRU-HULL CONNECTIONS. No cuffs required but may use #143 RHT cuffs.

Specifications

Construction:

Tube & Cover:
Corrugated white pvc
With hard pvc helix

Color: white

Reinforcement:
PVC

Temperature Range:
10°F to 120°F(-12°C to 49°C)

Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
	in.	mm.	in.	mm.	PSI Vac In./Hg	Bar	Lb./ 50 ft.	Kg/m	In.	mm.
146-0340	3/4	15.9	1.006	25.6	20	1.4	7	0.21	.75	19.1
146-1000	1	25.4	1.364	34.6	20	1.4	9	0.27	1.75	44.5
146-1120	1-1/2	38.1	1.724	43.8	28	1.9	15	0.45	2	50.8

*Burst Pressure is 4 x Working Pressure

Lengths:

Boxed, 50'(15.24m), **Coils** 100'(30.5M)

TRIDENT RUBBER INC.
585 PLUM RUN ROAD
CANONSBURG PA, 15317

1-800-414-2628

WWW.TRIDENTMARINE.COM



GENERAL
Marine
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand
Sales Ph +64 9 309 0048 · sales@generalmarine.co.nz
Service Ph +64 9 368 0938 · service@generalmarine.co.nz

www.generalmarine.co.nz